



Datasheet DALI hub IO module


Module with DALI interface, for integrating loads with DALI interface

Technical data


Power supply	24 VDC	
Max. power consumption	<5 W	
Inputs	Number of discrete inputs	6
	Inputs type	Dry contact
	Min. pulse width	30 ms
	Input interface	DALI
	Number of DALI devices	64
	Numbers of DALI groups	16
Interfaces	STARS interface	
Temperature	Operating: +5 °C ... +45 °C	
	Storing: -15 °C ... +50 °C	
Weight	116 g	
Size (DIN)	2 units	
Dimensions (W/H/D)	35 mm/107 mm/61 mm	
Mounting type	Din rail 35 mm	
Safety Rating	IP20	

Module address

Select device address by DIP switch on device



Wirings



Warnings



Before proceeding with the assembly, read instructions and schematics available at www.svit.io. Power supply, loads, other connectible stuff have to be in accordance with device specifications. Manufacture is not responsible for any damage caused by equipment, not connected in a proper way. In case of any questions, please, contact with support team at: www.svit.io/support

Cautionary statements



- Danger, caused by electric current
- Incorrect connections can cause an electric shock or fire
- All electric works can be done only appropriate qualified person
- During any works with device, make sure, that supply power is disconnected from the circuit

Manufacture information

NSA I.t.d
Syretska 28 str.
03128 Kyiv, Ukraine (UKR)

Warranty

Warranty information available at <https://svit.io/warranty>